

AD-A103 320

RAND CORP SANTA MONICA CA

F/6 20/4

THE H-R SUB X METHOD FOR PREDICTING TRANSITION, (U)

JAN 81 A R WAZZAN, C GAZLEY, A M SMITH

UNCLASSIFIED

RAND/P-6581

NL

1 OF 1
AD A
01062500

END
DATE
FILMED
10-81
DTIC

LEVEL II

(C)

AD A103320

THE H-R METHOD FOR PREDICTING TRANSITION

A. R. Wazzan, C. Gazley, Jr., A. M. O. Smith

(11/11)

DTIC
ELECTE
AUG 26 1981
H

January 1981

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

FAND/P-6581

81 8 25 096

DMC FILE COPY

The Rand Paper Series

Papers are issued by The Rand Corporation as a service to its professional Staff. Their purpose is to facilitate the exchange of ideas among those who share the author's research interests; Papers are not reports prepared in fulfillment of Rand's contracts or grants. Views expressed in a Paper are the author's own, and are not necessarily shared by Rand or its research sponsors.

The Rand Corporation
Santa Monica, California 90406

THE H-R_x METHOD FOR PREDICTING TRANSITION

A. R. Wazzan, C. Gazley, Jr., A. M. O. Smith

January 1981

DTIC
ELECTE
AUG 26 1981
S H D

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
Full Text	<input type="checkbox"/>
Unpublished	<input type="checkbox"/>
Classification	<i>Per</i>
<i>in a file</i>	
Distribution/	
Availability Codes	
and/or	
Special	
<i>A</i>	

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

THE $H-R_x$ METHOD FOR PREDICTING TRANSITION

A. R. Wazzan,* C. Gazley, Jr.** and A. M. O. Smith***

I. INTRODUCTION

This paper gives a brief description of a shortcut method, the $H-R_x$ method, for predicting transition in a wide class of boundary layer flows, including the effects of pressure gradient, surface heat transfer and suction. Here H and R_x are the body shape factor and the Reynolds number, based on distance x measured in the direction of the flow, respectively. The method is extremely simple to use and a good substitute to the well known but rather complicated e^9 method.

II. THE e^n METHOD OF FORECASTING TRANSITION

The $H-R_x$ method has not been correlated with test data but rather has been justified in terms of Tollmien-Schlichting waves and e^9 type calculations. Data are gradually being accumulated that show that the e^9 method is the best all around method that now exists for predicting boundary layer transition. Since the $H-R_x$ method is rooted in the e^9 method, we proceed to make some comments about the latter.

Transition, although it may commence with the amplification of Tollmien-Schlichting waves as described by linear stability theory, is dominated in its late stages by three dimensional and non-linear effects. Why then does transition occur at a disturbance amplification ratio a_t of about $a_t \approx e^9$ [1] as computed from linear instability theory?

The e^9 method is rooted in the following observations: Liepmann [2] hypothesized that at the breakdown to turbulence, the Reynolds stress $\tau = -\rho \overline{u'v'}$ due to the amplified fluctuations becomes comparable in magni-

* Consultant The Rand Corporation, Santa Monica, California; also Professor The University of California, Los Angeles.

** Consultant The Rand Corporation, Santa Monica, California; also Adjunct Professor The University of California, Los Angeles. Associate Fellow AIAA.

*** Adjunct Professor The University of California, Los Angeles. Fellow AIAA.

tude to the maximum mean laminar shear stress $\tau_L = \mu(\partial u/\partial y)$. The ratio τ/τ_L is given by

$$\tau/\tau_L = \frac{2}{c_{f_L}} \left[kb \left(\frac{u'_n}{u_e} \right)^2 a^2(x) \right]_{\max} \quad (1)$$

where c_{f_L} is the skin friction coefficient, u'_n is the disturbance amplitude at the neutral point, $b = v'/u'$ and $k = \overline{u'v'}/uv$, $a(x)$ is the amplification factor with respect to the neutral point, u and v are velocities in the x and y direction respectively and prime indicates disturbance values. Obrenski et al. [3] observes that in a low turbulence environment the critical Tollmien-Schlichting mode at the beginning of amplification may possess an amplitude u'_n of the order of $0.001\% u_e$, or perhaps even less; u_e is the edge velocity. Furthermore, Klebanoff et al. [4] found, in detailed examination of flat plate measurements, that disturbance growth via the laminar instability mechanism ceases to be valid when the rms velocity fluctuation v' in the boundary layer reaches $(u'/u_e)_{\max} \approx 0.015$, but that the first appearance of turbulent spots is expected at about $(u'/u_e)_{\max} \approx 0.20$. Assuming that these figures represent disturbance growth *not* only on a flat plate but *also* on airfoils and bodies of revolution, all at low free stream turbulence level, we find that amplification in the linear regime $[(u'/u_e)_{\max}/(u'_n/u_e) \approx 0.015/0.00001 = 1500 \approx e^{7.35}]$ substantially exceeds the amplification in the nonlinear regime $[0.20/0.015 \approx 13 \approx e^{2.6}]$. Total amplification $(= 0.20/0.00001)$ at transition is seen to be about $20,000 \approx e^{9.9}$; this amplification is of the same order as that reported by Michel [5], $e^{9.2}$, and computed by Smith et al. [6] and van Ingen [7] from linear instability theory. This amplification factor is consistent with the hypothesis of Liepmann. If we set $\tau/\tau_L = 1$, $(u'_n/u_e) \approx 0.00001$, $c_{f_L} \approx 0.664 R_L^{-1/2}$ with $R_L = 3 \times 10^6$ (for transition on a flat plate), $(u'/v')_{tr} = O(10)$ and $(uv/\overline{u'v'})_{tr} = O(10)$ at transition, then eq. (1) gives an amplification at transition $a(x_{tr}) \approx 1.4 \times 10^4 = e^{9.5}$. This suggests that

in boundary layer flows, where free-stream turbulence is very low, the growth of Tollmien-Schlichting waves controls the development to turbulent flow and so linear instability theory can be used as a basis for forecasting transition.

III. SOME PREDICTIONS FROM STABILITY THEORY AND THE e^9 METHOD

The factors being considered in this note, for either two-dimensional or axisymmetric low speed flow, are (1) effect of pressure gradient, (2) effect of suction, and (3) effect of wall heating or cooling. Figure 1 shows the results of calculations of the neutral stability point for wedge and other flows under a large variety of conditions. It contains results for an adiabatic flat plate with varying degrees of mass transfer, including the asymptotic suction case. The largest number of points are for various wedge flows in water with and without heat. The significant fact is that the neutral stability point when plotted in the form of the critical Reynolds number, R_{δ^*crit} , vs. H , the shape factor, this rather considerable variety of flows forms a *single* well defined curve. Shape factor is the immediate determinant of neutral stability rather than some more remote measure such as Hartree's β or Pohlhausen's Λ .

The present authors proceeded to determine if a similar correlation existed at transition as predicted by the e^9 method. Suction was not included in the study but a considerable number of wedge flows with various wall temperatures were studied for water. The results are shown in Figure 2, which also includes the data of Figure 1. But in Figure 2 the calculated values are plotted in terms of R_x vs. H rather than R_{δ^*} vs. H . Again, except for the highest temperature differentials the data form well defined curves; the scatter is so small that suction effects would undoubtedly fall along the same curve. The correlation indicates that the neutral and transition points are primarily a function of H . Pressure gradient, heating

and suction are only methods of influencing H . The results of Figure 2 are only for two-dimensional and similar flows, but they suggest a method of predicting transition: for the conditions of the problem, make a plot of H vs. R_x , from ordinary boundary layer calculations, as one proceeds back along the body. The plot will always start beneath the two loci of Figure 2. When the curve crosses the e^9 locus, transition should occur. An equation that fits the e^9 locus very well is (for bodies of revolution R_x is replaced with R_s where s is the distance measured along the surface of the body):

$$\log[R_x(e^9)] = -40.4557 + 64.8066H - 26.7538H^2 + 3.3819H^3, \quad (2)$$

$$2.1 < H < 2.8$$

IV. THE H - R_x METHOD FOR PREDICTING TRANSITION OVER A BODY OF REVOLUTION

Because the correlations of Figures 1 and 2 are for two-dimensional similar flows, as a sample problem we chose a heated Reichardt body of revolution moving in 67°F, 19.44°C, water at a velocity that gives $u_\infty/\nu = 6 \times 10^6/\text{ft}$, $20 \times 10^6/\text{m}$, Figure 3. Because there is a stagnation point the flow starts out very stable (low H). For the case of no heating ($\Delta T = 0^\circ\text{C}$) the neutral point is crossed at $R_x \approx 10^6$ and transition occurs between $R_x = 3$ and 4×10^6 . The circle is for the full e^9 calculation, so the agreement is perfect. With 10°F (5.5°C) of heating, the boundary layer is more stable and now the neutral point is crossed at about $R_x = 1.2 \times 10^6$ and transition is moved back to about $R_x = 9 \times 10^6$. Again the agreement with the full e^9 method is very good. At a heating of 20°F (11.1°C) transition is moved still further back but the agreement with the full e^9 calculation is not quite as good. But the example shows clearly the method of prediction and that the correlation seems to work even when the flow is nonsimilar and non-two-dimensional.

For a practical shape such as in this example, the H - R_x trace meanders. For a pure similar flow the trace would be vertical. If there is a sudden

change in pressure gradient, suction or heat the trace would be horizontal for some distance. Note that only ordinary but accurate boundary layer calculations of H vs. R_x are needed for transition prediction, not lengthy stability calculations.

V. DISCUSSION

Other simple methods of predicting transition lack the generality of the H - R_x method because they are correlations based on parameters that are more removed from the best measure of stability, H . Michel's method for instance is an excellent correlation method, correlating R_θ vs. R_x at transition for two-dimensional incompressible flow, e.g., airfoils. But when bodies of revolution, heat, or suction are considered the correlation is no longer applicable. The same kind of trouble applies to methods like Granville's [8], which correlates with a pressure gradient parameter such as Pohlhausen's Λ . Obviously this kind of method fails if other means than pressure gradients are used to affect transition. Consider a fixed point on a particular body. That point has one value of Λ regardless of the degree of suction or heating. But if H is used as the correlating parameter, changes at that point in the boundary layer flow, as by heating or suction, manifest themselves in changes in H . However, we must stress that when there is heat transfer more than the shape factor is involved, particularly if temperature differences are high. For instance, in the full e^9 method using the extended Orr-Sommerfeld equation [1], additional terms such as $d^2\mu/dy^2$ enter the stability problem in addition to the basic velocity profile data that determines H . Note that the correlation is poor at high heating rates where $H < 2.1$, Figure 2.

The H - R_x method for predicting transition gives reasonable answers so long as the flow does not vary too much from nearly similar flow, i.e., local

similarity. Also it is applicable only so long as the effects of surface roughness, vibrations and freestream turbulence level are sufficiently low, just as required for the basic e^9 method. The method is also restricted to heating rates where $T_w - T_\infty$ does not exceed about 23°C.

The correlation has been developed entirely theoretically using the e^9 method as if it were exact for predicting transition. No attempt has been made to develop the correlation from experimental data, partly because of the labor involved but partly because good test data are quite scarce for unusual conditions such as heating in water. The main fact that can be claimed therefore is that the $H-R_x$ method is a very convenient substitute for calculating nearly the same results as the full e^9 method. Also of course this sample case is not the only one that has been studied; the $H-R_x$ method has been used extensively in other studies with plausible predictions, and a number of other comparisons with the full e^9 method have been made. Where the flow differs widely from the conditions of the correlation, a check should be made by the full e^9 method. But for a large range of practical conditions, the $H-R_x$ method seems accurate, convenient and quite general.




Figure 1




Figure 2




Figure 3

REFERENCES

1. Wazzan, A. R., Gazley, C., Jr., and Smith, A. M. O., "Tollmien-Schlichting Waves and Transition", Prog. Aerospace Sci., Vol. 18, pp. 351-392, Pergamon Press, London 1979.
2. Liepmann, H. W., "Investigations of Laminar Boundary-Layer Stability and Transition on Curved Boundaries", NACA Adv. Conf. Rept. No. 3H30, later W-107, 1943.
3. Obrenski, H. J., Morkovin, M. V., Landahl, M., with contributions from Wazzan, A. R., Okamura, T. T., and Smith, A. M. O., "A Portfolio of Stability Characteristics of Incompressible Boundary Layers", AGARDO-GRAPH No. 134, NATO, Paris, 1969.
4. Klebanoff, P., Tidstrom, K. D., and Sargent, L. M., "The Three-Dimensional Nature of Boundary Layer Instability", J. Fluid Mech., Vol. 12, 1962, pp. 1-34.
5. Michel, R., "Etude de la Transition sur les Profils d'aile-Etablissement d'un Point de Transition et Calcul de la Trainee de Profil en Incompressible", ONERA, Rapport 1/1758A, 1951.
6. Smith, A. M. O., and Gamberoni, H., "Transition, Pressure Gradient and Stability Theory", Douglas Aircraft Company, Long Beach, CA, Report ES26388, 1956.
7. van Ingen, J. L., "A Suggested Semi-Empirical Method for the Calculation of Boundary Layer Transition Region", Univ. of Technology, Dept. of Aero. Engr., Delft, The Netherlands, Report VTH-74, 1956.
8. Granville, P. S., "Comparison of Existing Methods for Predicting Transition from Laminar to Turbulent Flow on Bodies of Revolution", Naval Ship Research and Development Center, TN 111, 1968.

9. Tsou, F. K., and Sparrow, E. M., "Hydrodynamic Stability of Boundary Layer with Surface Mass Transfer", Appl. Sci. Res., Vol. 22, 1970, pp. 273-286.
10. Hughes, T. H., and Reid, W. H., "On the Stability of the Asymptotic Suction Boundary Layer Profile", J. Fluid Mech., Vol. 23, 1965, pp. 715-735.
11. Wazzan, A. R., Okamura, T. T., and Smith, A. M. O., "Spatial and Temporal Stability Charts for the Falkner-Skan Boundary Layer Profiles", Douglas Aircraft Company, Long Beach, CA, Report No. DAC-6708, Sept. 1968.

LIST OF FIGURES

- Figure 1 Critical Reynolds number R_{δ^*crit} vs. H .
- Figure 2 Critical and transition (computed) Reynolds number for adiabatic and heated wedge flows in water. β is Hartree's β .
- Figure 3 Paths of boundary-layer development (H vs. R_X) and predicted transition for a 13:1 Reichardt body. Comparison with heated wedge-flow predictions. Circles denote point where $Re_{s(e^9)}$ is reached, $u_\infty/\nu = 6 \times 10^6/\text{ft}$, $20 \times 10^6/\text{m}$. s is length measured along the body surface.